


## CAPFCU-B25 Modular Connectors - FIELD CRIMPED PLUG 8MOD (RJ45) CAT6/6A UTP KIT



For more Information  
please call

1-800-Belden1



### General Description:

FIELD CRIMPED PLUG 8MOD (RJ45) FIELD CAT6/6A UTP (25-PACK)

### Usage (Overall)

<b>Suitable Applications:</b>	TIA Category 6 & TIA Category 6A, ISO Class E, ISO Class EA, 1000BASE-T, 10GBase-T
<b>Related Parts:</b>	Boot CB6MM, Boot CB7MM & Boot CB8MM , Recommended CAT6 & CAT6A UTP cables (Solid & Stranded).

### Physical Characteristics (Connectivity)

#### Dimensions

Dimensions:

Height (in.)	Width (in.)	Length (in.)
0.312	0.460	0.885

#### Materials

Materials:

Description	Type	Material
Plug	RJ45	Polycarbonate
Contact		Phosphor Bronze Alloy Plated with 50u inch Gold

#### Color

<b>Color:</b>	Clear
---------------	-------

#### Weight

<b>Weight:</b>	0.085 lbs.
----------------	------------

#### Included Parts

<b>Included Parts:</b>	RJ45 Plug, Load Bar, Wire guide, Installation Guide.
------------------------	--

#### Packaging

<b>Packaging:</b>	Kit of 25 units per Bag.
-------------------	--------------------------

### Mechanical Characteristics (Connectivity)

Termination Interface:

Termination	Connection	Durabilities
RJ45	Mated Connection	1000 Cycles

<b>Operating Temperature Range:</b>	-40°C To +85°C
-------------------------------------	----------------

<b>Tool Compatibility:</b>	Crimping Tool CTPFC01
----------------------------	-----------------------

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>UL Rating:</b>	94V-0
<b>Other Standards:</b>	FCC Part 68, Subpart F, IEC 60603-7
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	07/01/2006
<b>Telecommunications Standards:</b>	Category 6 - TIA 568.C.2, Category 6A - TIA 568.C.2, ISO/IEC 11801:2002 Ed.2
<b>Other Specification:</b>	Complies with ANSI/TIA-1096-A Requirements.

#### Suitability

<b>Suitability - Indoor:</b>	Yes - Indoor
------------------------------	--------------

## CAPFCU-B25 Modular Connectors - FIELD CRIMPED PLUG 8MOD (RJ45) CAT6/6A UTP KIT

### Transmission Characteristics (Connectivity)

<b>Mated Connection Table - Footnote:</b>	* Category 6 - TIA 568.C.2 when tested with Recommended CAT6 Cables. Category 6A - TIA 568.C.2 when tested with Recommended CAT6A Cables.
<b>Dielectric Strength:</b>	1,000 V RMS @ 60 Hz for 1 minute
<b>Current Rating:</b>	1.500 A
<b>Insulation Resistance:</b>	500 M-Ohm Minimum
<b>Max. Contact Resistance:</b>	10 m-Ohm

### Notes (Overall)

<b>Notes:</b>	For additional information about this product, refer to Installation Guide PX106195, or visit our web at <a href="http://www.belden.com">http://www.belden.com</a>
<b>Notes (Cont'd.):</b>	Suitable for Conductors with insulation OD range 0.037~0.045 in. and for Cable OD range 0.23~0.31 in. (6~8 mm ). Please refer to the cable-plug compatibility guide 'Plug Compatibility Matrix V1 ECOS BDC 0415 A AG' for proper pairings.

### Product Family

#### Part Number List:

Description	Part Number
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT5E SHIELDED (25-PACK)	C5PFCF-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT5E/6 UTP (25-PACK)	C6PFCU-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT6/6A UTP (25-PACK)	CAPFCU-B25
8MOD (RJ45) FIELD CRIMPED PLUG KIT CAT6/6A SHIELDED (25-PACK)	CAPFCF-B25
BOOT 6MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB6MMBK-B100
BOOT 7MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB7MMBK-B100
BOOT 8MM FOR FIELD CRIMPED PLUG, BLACK (100-PACK)	CB8MMBK-B100
CRIMPING TOOL FOR FIELD RJ45 PLUG	CTPFC01

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
CAPFCU-B25	1 EA	0.085 LB			CAT6/6A FIELD CRIMPED PLUG KIT

Revision Number: 0    Revision Date: 04-23-2015

© 2016 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.