# Product Data Sheet

🖀 1-888-452-HANA (4262) 📮 info@hanawireless.com

☑ 9465 Southampton Pl, Boca Raton, FL 33434, USA



## Model: HW2-N14-1V

14x12x7 Inch Weatherproof Enclosure with120 Vac Mounting Plate, Vent System



#### Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- Integral mounting flange, mast mounting option
- Aluminum mounting plate with 120 Vac outlets, ventilation system, patented (US8014157) slotted accessory mounting design

#### Applications

- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage

## Specifications

ColorTool Gray – RAL 7035Voltage   Vac120Heater   F° (C°)N/AHeat Temperature ON/OFF   F° (C°)N/AFan Power   WattN/AFan Temperature ON/OFF   F° (C°)N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   Ib (kg)12.5 (5.7)Outside Dimensions   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V		
Voltage   Vac120Heater   F° (C°)N/AHeat Temperature ON/OFF   F° (C°)N/AFan Power   WattN/AFan Temperature ON/OFF   F° (C°)N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   Ib (kg)12.5 (5.7)Outside Dimensions   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Material	FRP
Heater   F° (C°)N/AHeat Temperature ON/OFF   F° (C°)N/AFan Power   WattN/AFan Temperature ON/OFF   F° (C°)N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   Ib (kg)12.5 (5.7)Outside Dimensions   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Color	Tool Gray – RAL 7035
Heat Temperature ON/OFF   $F^{\circ}(C^{\circ})$ N/AFan Power   WattN/AFan Temperature ON/OFF   $F^{\circ}(C^{\circ})$ N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   lb (kg)12.5 (5.7)Outside Dimensions, Max   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Voltage   Vac	120
Fan Power   WattN/AFan Temperature ON/OFF   F° (C°)N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   lb (kg)12.5 (5.7)Outside Dimensions, Max   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Heater   F° (C°)	N/A
Fan Temperature ON/OFF   F° (C°)N/AMounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   lb (kg)12.5 (5.7)Outside Dimensions, Max   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Heat Temperature ON/OFF   F° (C°)	N/A
Mounting Plate Dimensions   in (mm)N/AMounting Plate MaterialAnodized AluminumWeight   lb (kg)12.5 (5.7)Outside Dimensions, Max   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Fan Power   Watt	N/A
Mounting Plate MaterialAnodized AluminumWeight   lb (kg)12.5 (5.7)Outside Dimensions, Max   in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions   in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5V	Fan Temperature ON/OFF   F° (C°)	N/A
Weight   lb (kg) 12.5 (5.7)   Outside Dimensions, Max   in (mm) 15.5 (393) x 13.5 (342) x 8.7 (220)   Inside Dimensions   in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147)   Flame Rating UL 94-5V	Mounting Plate Dimensions   in (mm)	N/A
Outside Dimensions, Max   in (mm) 15.5 (393) x 13.5 (342) x 8.7 (220)   Inside Dimensions   in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147)   Flame Rating UL 94-5V	Mounting Plate Material	Anodized Aluminum
Inside Dimensions   in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147)   Flame Rating UL 94-5V	Weight   lb (kg)	12.5 (5.7)
Flame Rating UL 94-5V	Outside Dimensions, Max   in (mm)	15.5 (393) x 13.5 (342) x 8.7 (220)
	Inside Dimensions   in (mm)	13.5 (343) x 11.5 (292) x 5.8 (147)
RoHS Compliant	Flame Rating	UL 94-5V
Compilant	RoHS	Compliant
Environmental Rating   NEMA - IP 3R, 3RX - 24	Environmental Rating   NEMA - IP	3R, 3RX - 24
Cable Feed 1/2in Conduit Connector	Cable Feed	1/2in Conduit Connector

### **Package Specifications**

Package Quantity	1 per Carton
Length   in (mm)	16.4 (417)
Width   in (mm)	14.0 (356)
Depth   in (mm)	13.2 (335)
Weight   lb (kg)	13.0 (5.9)

## Wireless That Works



