



Features

- (2) 4 Inch Vents with Rain Shields and Screens
- Water Resistant JIC Enclosure Design with Gasketed Lid
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Raised Bosses with Threaded Brass Inserts for Plate Mounting
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Cable Glands and Stainless Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF141210V** features two 4 inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting equipment from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Extreme Protection Built to Last

This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. The enclosure features a gasketed door with stainless steel continuous hinge and stainless-steel quick release latches with padlock hasps.

Increased Interior Space

The NF141210 series enclosures feature an extra deep lid, almost 2 inches deeper than our NF141208 series enclosures. With the generous size of this enclosure and extended lid the NF141210 can accommodate a wide range of equipment.

Cable Glands

The enclosure features our unique PG-16 cable glands with a closed inner seal. They are installed in the open ports to maintain the NEMA rating of the enclosure when not in use. When required for use, simply punch a hole through the inner membrane, run your cables and tighten for a water-tight seal.

Mounting

Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	15.7 x 13.8 x 12.2 Inches (401 x 352 x 311 mm)
Inner Dimensions*	13.0 x 11.0 x 9.7 Inches (330 x 279 x 246 mm)
Weight	11.3 lbs. (5.1 kg)
Ratings	NEMA 3R, 3RX / IP24
Flame Rating	UL94-5V
Industry Certifications	CE

*Interior dimensions represent maximum space available for equipment.