



Features

- Two (2) 4" Vents with Rain Shields and Screens
- (4) Pre-Wired 120VAC Outlets with Removable 120VAC Terminal Block
- Aluminum Equipment Mounting Plate
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Cable Glands and Stainless Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF141210VA1** features two 4" vents with rain shields and cleanable screens. The rain shields help keep rainwater from entering the enclosure while allowing ventilation of installed equipment or batteries while maintaining weatherproof protection.

The aluminum equipment mounting plate features four pre-wired 120VAC power outlets and a terminal strip, for easy wiring by a qualified installer.

Extreme Protection Built to Last

This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. It features a gasketed door with stainless steel continuous hinge and stainless-steel quick release latches with padlock hasps.

Increased Interior Space

The NF141210 series enclosures feature an extra deep lid, almost 2 inches deeper than our NF141208 series enclosures. With the generous size of this enclosure and extended lid the NF141210 can accommodate a wide range of equipment.

Removable Terminal Block

This enclosure features our 120VAC top entry terminal block. It is easily removable which helps simplify on-site wiring. It can accept wires sizes from 12 to 18 AWG. The wires are secured by side terminal screws.

Mounting

Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Voltage	120VAC
Max Load	15A @ 120VAC
Outer Dimensions	15.7 x 13.8 x 12.2 Inches (401 x 352 x 311 mm)
Inner Dimensions*	13.0 x 11.0 x 8.7 Inches (330 x 279 x 222 mm)
Mounting Plate Material	0.10 in (2.5 mm) Aluminum
Mounting Plate Dimensions	10.9 x 12.8 in. (276 x 324 mm)
Weight	13 lbs. (5.9 kg)
Terminal Block Wire Range	12-18 AWG
Terminal Block Wire Strip Length	6-7mm
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	UL94-5V

*See drawing for detailed dimensions of maximum space available for equipment.