Drip Rail

Equipment Mounting Plate

Dual Quarter-Turn Latches with Removable Keys

120VAC Outlets

Gasketed Door

Fiberglass Reinforced Polyester (FRP) Construction

Ground Lug

Cable Glands

Wall Mounting Feet, (4) Included with Enclosure

Features

- Heavy Duty Fiberglass Reinforced Polyester (FRP) Construction
- Aluminum Equipment Mounting Plate
- (2) Pre-Wired 120VAC Power Outlets
- Dual Quarter-Turn Door Latches with Removable Keys
- (4) Mounting Feet Included
- NEMA Type 3, 3X / IP65 Rated
- Optional Lockable Latch Sets Available

Description

The **Altelix NFC20608A1** NEMA 3X / IP65 rated enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP). The door is fully gasketed making this enclosure suitable for use indoors or outdoors. The lockable door features reinforced hinges and dual quarter-turn latches to secure the enclosure and is locked and unlocked using the included removable keys. A drip rail over the door provides additional protection against water dripping into the cabinet while the enclosure is wet.

Aluminum Equipment Mounting Plate
This configuration consists of the fiberglass NEMA enclosure with hinged lid and a 0.10" (2.5mm) thick aluminum plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

120VAC Power
Two pre-wired 120VAC power outlets are provided inside the enclosure to power equipment. The outlet box is easily removable to facilitate wiring to an external power source.

Mounting
Four mounting feet are included so that the enclosure can be securely mounted to a wall or other structure. Optional flange and pole mounting kits are available.

Optional Lockable Latches
For additional protection of internal equipment installed, optional keyed latch sets are available. These optional lockable latches are direct replacements for the standard quarter-turn latches that come pre-installed in the enclosure.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Light Gray
Voltage / Max. Load	120VAC / 15A @ 120VAC
Outer Dimensions (Height x Width x Depth)	19.7 x 15.8 x 7.9 Inches (500 x 402 x 200 mm)
Inner Dimensions* (Height x Width x Depth)	14.2 x 14.2 x 6.0 Inches (362 x 362 x 152 mm)
Equipment Plate Material	0.10 In. (2.5 mm) Aluminum
Equipment Plate Dimensions	13.7 x 17.9 In. (348 x 455 mm)
Weight	14.2 lbs. (6.4 kg)
Ratings	NEMA Type 3, 3X / IP65

*Interior dimensions represent maximum space available for equipment.