



## Features

- Heavy Duty Fiberglass Reinforced Polyester (FRP) Construction
- Aluminum Equipment Mounting Plate
- Thermostat Controlled 200W Heating System
- (2) Pre-Wired 120VAC Power Outlets
- Dual Quarter-Turn Door Latches with Removable Keys
- (4) Mounting Feet Included
- NEMA Type 4, 4X / IP66 Rated
- Optional Lockable Latch Sets Available

## Description

---

The **Altelix NFC201608HA1** NEMA 4X / IP66 rated enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP). The door is fully gasketed making this enclosure suitable for use indoors or outdoors. The lockable door features reinforced hinges and dual quarter-turn latches to secure the enclosure and is locked and unlocked using the included removable keys. A drip rail over the door provides additional protection against water dripping into the cabinet while the enclosure is wet.

**Aluminum Equipment Mounting Plate** - This configuration consists of the fiberglass NEMA enclosure with hinged lid and a 0.10" (2.5mm) thick aluminum plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

**120VAC Power** - Two pre-wired 120VAC power outlets are provided inside the enclosure to power equipment. The outlet box is easily removable to facilitate wiring to an external power source.

**200W Heating System** - Ideal for extreme cold environments, this model also features a 200W thermostat-controlled heater. The heater is situated below the mounting plate and wired internally it does not interfere with user installed equipment or require the use of the AC outlets.

**Mounting** - Four mounting feet are included so that the enclosure can be securely mounted to a wall or other structure. Optional flange and pole mounting kits are available.

## Specifications

---

<b>Material</b>	Fiberglass Reinforced Polyester
<b>Color</b>	Light Gray
<b>Voltage / Max. Load</b>	120VAC / 15A @ 120VAC
<b>Heater Turn-On Temperature</b>	43°F (6°C)
<b>Heater Turn-Off Temperature</b>	59°F (15°C)
<b>Heater Power</b>	200 Watt
<b>Outer Dimensions</b> (Height x Width x Depth)	19.7 x 15.8 x 7.9 Inches (500 x 402 x 200 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	14.2 x 14.2 x 4.5 Inches (362 x 362 x 114 mm)
<b>Equipment Plate Material</b>	0.10 In. (2.5 mm) Aluminum
<b>Equipment Plate Dimensions</b>	13.7 x 17.9 In. (348 x 455 mm)
<b>Weight</b>	16 lbs. (7.2 kg)
<b>Ratings</b>	NEMA Type 4, 4X / IP66

\*Interior dimensions represent maximum space available for equipment.