




Technical Data Sheet

ONE² 18Gbps Passive HDMI Cable



The Kordz ONEv2 HDMI Cable is the professional grade passive HDMI cable designed to provide reliable, economical, uncompressed 4K connectivity for high volume commercial integration projects. It delivers full 18Gbps performance at every length up to 5m. Its slim, flexible, fire-rated PVC jacket and compact connector ensure durability, easy routing and secure connections, even in tight spaces. Supplied in eco-friendly recyclable paper packaging, the ONEv2 HDMI Cable is quick to open, easy to clean up, and comes backed by the Kordz lifetime warranty for peace of mind.

- Full 18Gbps bandwidth for reliable uncompressed 4K signal at all lengths up to 5m
- Compact connector assembly rated for 1kg retention force
- Flexible, slim, fire-rated PVC jacket for easy installation in tight spaces
- Supplied in eco-friendly recyclable, quick-to-open paper packaging with hang tab
- Individually tested for consistent performance that's 'Connectivity Assured'
- Designed for economical, high-volume commercial integration projects
- Lifetime warranty for peace of mind



Technical Specifications

| Performance | | 0.5m to 5.0m Lengths |
|---------------------------|------------|--|
| HDMI Certification | | High Speed with Ethernet |
| Supported Data Rate | | ≥ 6.0Gbps, 17.82Gbps agg (4K UHD) |
| HDMI Clock | | CEC, Auto Lip-Sync Correction, Ethernet channel, ARC, eARC, High Dynamic Range (HDR) |
| Construction | | |
| Conductors | | Solid 32-28 AWG OFC, length dependent |
| Insulation | | Polypropylene |
| Shielding | TMDs Pairs | AL/Mylar, 125% Coverage |
| | Overall | AL/Mylar, 125% Coverage + Al-Mg Braid 65% Coverage |
| | | AL/Mylar, 125% Coverage + Tinned copper braid, min 85% coverage |
| Cable Jacket Material | | 0.5 - 2.0m: VW-1 3.0 - 5.0m UL CMG fire-rated PVC composite materials |
| HDMI Connector Shell | | Premium gauge folded steel, 1μ" Ni-plated |
| HDMI Connector Pins | | Solid OFC, 15μ" 24K Gold plated |
| Termination | | High frequency soldering |
| HDMI Back-shell | | PVC glossy front shell with PVC injection moulded boot and strain relief |
| Mechanical | | |
| Cable Diameter | | 0.5m-3.0m: 5.10±0.15mm/0.201in Ø 4.0m-5.0m: 6.50±0.15mm/0.256in Ø |
| Mounting Depth | | 0.5m-3.0m: 20.0mm/0.79in Ø 4.0m-5.0m: 22mm/0.87in Ø |
| Cable Bend Radius | | 0.5m-3.0m: 25.50mm/1.00in Ø 4.0m-5.0m: 32.50mm/1.28in Ø |
| Connector Retention Force | | 1kgf / 10N (nominal) |

| Part No | Length | Fire Rating | Master Ctn Qty | Master Ctn Size |
|----------------|--------|-------------|----------------|--|
| K16015-0050-CH | 0.5m | VW-1 | 80 | 290mm x 264mm x 282mm 11.42in x 10.39in x 11.10in |
| K16015-0100-CH | 1.0m | | 72 | |
| K16015-0150-CH | 1.5m | | 64 | |
| K16015-0200-CH | 2.0m | | 56 | |
| K16015-0300-CH | 3.0m | | 52 | |
| K1601G-0400-CH | 4.0m | UL CMG | 42 | 558mm x 298mm x 240mm 21.97in x 11.73in x 9.45in |
| K1601G-0500-CH | 5.0m | | 36 | |