



Technical Data Sheet

PRO³ Active Optical HDMI cables



Making performance easier

The Kordz PRO³ Active Optical HDMI Cables exceed the standards of performance and flexibility, delivering 18Gbps 4K resolution over long distances and optimised through Active Optical Technology. Fully shielded high quality ABS shells and with 1Kg connectors provide resilience in demanding applications where a cost- effective, reliable solution is required. Fit Kordz PRO³ Active Optical HDMI Cables with confidence, backed by the Kordz warranty.


- Solid 1Kg grip, ensuring connectors stay in place for as long as required Compact 18mm wide ABS headshell for easy installation
- Reinforced internals for superior flexibility and pull strength during installation
- A lightweight and UL CMG fire-rated jacket for safety
- No external power dependencies, it works like a normal passive HDMI cable
- 18Gbps certification from DPL Labs
- High contrast detailed labelling with inventory management design
- Available in 10m, 15m, 20m




4K 60Hz 4:4:4 Gbps	HDR	ARC	CMG FIRE RATED	2 (YEAR) WARRANTY
-----------------------	-----	-----	-------------------	----------------------

Technical Specifications				
HDMI Cable Certification		10.0-20.0m ACTIVE OPTICAL		
DPL Labs Certified Data Rate		6.0Gbpsc, 17.82Gbps agg		
Supported Data Rate		≥ 6.0Gbpsc, 17.82Gbps agg (4K UHD)		
HDMI Clock		340MHz		
Construction				
TMDS		OM3 (50/125) optical fibre		
4C + HEAC Pairs	Conductors	Tinned copper, 32-26AWG		
	Insulation	Foamed PE / HDPE		
Overall Shielding		AL/Mylar		
Cable Jacket Material		UL CMG fire-rated PVC composite materials		
HDMI Connector Shell		Premium gauge folded steel, 1µ" 24K Gold-plated		
HDMI Connector Pins	connector Pins Solid OFC, 18µ" 24K Gold-p			
Active Optical Technology	al Technology Directional, In-shell Optical Light Engi			
HDMI Backshells		ABS front shell with PVC injection moulded boot and strain relief		
Mechanical				
Cable Diameter	le Diameter 4.70mm 0.1			
Mounting Depth		62.0mm 2.5in		
Cable Bend Radius		20.0mm 0.78in		
Connector Retention Force		10N (1kg / 2.2lbs) +10/-5%		

Part No:	Length	Inner Ctn Qty	Master Ctn Qty
K26216-1000-CH	10.0m 32'9"	15	90
K26216-1500-CH	15m 49'2"	12	72
K26216-2000-CH	20m 65'6"	10	60





Kordz products are sold with a limited warranty as outlined at: www.kordz.com@2021 Kordz International. All rights reserved. Kordz Connectivity. Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries. All other trademarks are the property of their respective owners.